

Agency Name:

Address:

**Quotation for Dismantled and removed old chairs from Kairali/Sree
Theatres, Thrissur**

Sl.no	Description of item	Unit	Qty.	Rate (Rs) in		Amount
				Figure	words	
	Dismantled and removed old chairs from Kairali/Sree Theatres, Thrissur					
1.	<p><u>Push back Chairs</u></p> <p><u>Chairs of size – balcony seats (overall in normal position):</u> 550mm wide from the centerlines of arm rests, 600mm width from front to back, 1000mm total height on back side or nearest with the following specifications. (Kairali – 165 & Sree – 139 nos)</p> <p><u>Side stands:</u></p> <p><u>560 x 300mm or nearest size</u></p> <p>Made up of and 25 x 25mm – 16swg / 40 x 20mm – 18swg C.R sq. tube and 25 x 6mm M.S flat to meet the structural requirements and sides covered with either 22 swg C.R sheets or 6mm thick upholstered board. Every end row of legs completely covered with the fabric upholstery boards. All the metal parts painted 2 coats of enamel paint after a priming coat or powder coated.</p> <p><u>Seats:</u></p> <p><u>430/460 x 430 mm or nearest size</u></p> <p>Seat frames fabricated and made to shape with 25 x 25mm – 18 swg / 18 x 18mm-</p>	Each	304			

	<p>16swg C.R sq. tubes and bottom covered with 22g C.R sheet/12 x 3mm flats in suitable spacing and upholstered with 100mm average thickness cold-molded Polyurethane foam of density 45-50kg/cu.m and 15mm thick 'U' foam over it made to shape and finally covered with foam backed fire retardant and scotch guard treated fabric of approved quality and colour.</p> <p><u>Backrests:</u></p> <p><u>760 x 430/460 mm or nearest size</u></p> <p>Backrests frames fabricated and made to shape with 25 x 25mm – 18 swg/18 x 18mm- 16swg C.R sq. tubes and covered inner portion with 22g C.R sheet/12 x 3mm flats in suitable spacing and shape and upholstered with 75mm av. thick cold-molded Polyurethane foam of density 45-50kg/cu.m and 15mm thick 'U' foam over it made to shape in bucket type and finally covered with foam backed and scotch guard treated fabric of approved quality and colour. Rear side of the backrest covered with cup type 5mm thick PPCP (Plastic Molded to shape). The backrests have head rest and lumbered supports.</p> <p><u>Arm rests:</u></p> <p>450 x 55 x 50 mm or nearest size made up of injection-molded polypropylene plastic with the cup holder.</p>						
2.	<p><u>Lower class Chairs of back push type of overall size (in normal position):</u> 500mm wide from the centrelines of arm rests, 500mmwidth from front to back, 1000mm total height on back side or nearest sizes with the following specifications. (Kairali – 520 & Sree – 244</p>	Each	764				

nos)

Side stands:

560 x 300mm or nearest of overall size

Made up of and 25 x 25mm – 16swg / 40 x 20mm – 18swg C.R sq. tube and 25 x 6mm M.S flat to meet the structural requirements and sides covered with either 22 swg C.R sheets or 6mm thick upholstered board. Every end row of legs completely covered with the fabric upholstery boards. All the metal parts painted 2 coats of enamel paint after a priming coat or powder coated.

Seats :430/450 x 430 mm or nearest size

Seat frames fabricated and made to shape with 25 x 25mm – 18 swg / 18 x 18mm- 16swg C.R sq. tubes and bottom covered with 22g C.R sheet/12 x 3mm flats in suitable spacing and upholstered with 100mm average thickness cold-moulded Polyurethane foam of density 45-50kg/cu.m and 15mm thick 'U' foam (if necessary) over it made to shape and finally covered with foam backed fire retardant and scotch guard treated fabric of approved quality and colour.

Backrests of back push type:

660 x 430/450 mm or nearest size

Backrests frames fabricated and made to shape with 25 x 25mm – 18 swg/18 x 18mm- 16swg C.R sq. tubes and covered inner portion with 22g C.R sheet/12 x 3mm flats in suitable spacing and shape and upholstered with 75mm or nearest av. thick cold-moulded Polyurethane foam of density 45-50kg/cu.m and 15mm thick 'U' foam(if necessary) over it made to shape in bucket type and finally covered with

<p>foam backed and scotch guard treated fabric of approved quality and colour. Rear side of the backrest covered with cup type 5mm thick PPCP (Plastic Moulded to shape)or pressed cup type 0.7mm thick C.R sheet with powder coat finishing. The backrests have head rest and lumbered supports.</p> <p>Arm rests:</p> <p>450 x 55 x 50 mm or nearest size made up of injection-moulded polypropylene plastic with the cup holder.</p>							
<p>Total Number of Dismantled and removed old Seats 1068</p>							
<p>TOTAL AMOUNT</p>							

Signature of Bidder